



LumiFlex LED Neon - LDNF315SVR




Side View 270deg RGBWhite Colour Changing 17W IP68

SPECIFICATION

CODE	LDNF315SVR
COLOUR	RGBWhite Colour Changing
WATTS	17W/m
VOLTS INPUT	24VDC
AMPS INPUT	0.71Amps/m
IP RATING	IP68
DIM	Yes by PWM
WORKING TEMP	-30 to +45deg C
LED	Epistar 5050
WARRANTY	3years
MAX RUN	8m single feed or 16m double feed
BEND RADIUS	40mm minimum
BEAM ANGLE	270deg approx
CUT LENGTH	100mm (6 LEDs)
FIXING	By profile or clips
CONNECTION	Factory moulded cable entry

DIMENSIONS



FEATURES:

- # Continuous linear light with no spotting.
- # UV stabilised PVC & chlorine resistant.

APPLICATIONS:

- # Accent lighting in exterior applications.
- # Exterior steps & seating.
- # High lighting buildings
- # Creating sculptural luminous forms.

NOTE:

- # Cable entry type & cable length need to be specified.
- # When feeding from both ends its best practice for cable lengths to be the same.
- # Note that lengths will be cut down to the nearest cut point see "Cut Length" above.
- # Note bend direction diagram. Great care must be taken on install to bend only in the direction shown or risk breaking the LED circuit board & voiding the warranty.

