



LCDMSD-DA4

DALI DT6 Dim Slave 12-48VDC 4X5A IP20

PRODUCT OVERVIEW

The DA4 is a 4 channel constant voltage DALI LED controller supports 12-48V operation with 3A or 5A output per channel, delivering powerful and flexible lighting control. It utilises PWM digital dimming with a standard DALI logarithmic dimming curve for smooth, accurate performance. Designed with four DALI address inputs and four channel outputs, each address is automatically assigned by the DALI master controller for straightforward setup. For larger lighting loads, the system can be easily expanded using compatible data repeaters.

PRODUCT INFORMATION

CODE

LCDMSD-DA4

VOLTAGE OUTPUT

12-48VDC

OUTPUT CURRENT (PER CH)

5A/ch@12-24V, 3A/ch@48V

DIMMING INPUT

DALI

DIMMING RANGE

0-100%

REMOTE ENABLED

No

SAFETY

AS/NZS61347 EN55015

IP RATING

20

DIMENSIONS

L178mm x W38mm x H27mm

VOLTAGE INPUT

12-48VDC

OUTPUT POWER

576W

CHANNELS

4

DIMMING OUTPUT

PWM

PWM FREQUENCY

2kHz

STANDBY LOAD

0.5W

PROTECTION

Reverse polarity, Overheat,
Overload & Short circuit

OPERATING TEMP

-30°C to 55°C

DIMENSIONS

