



LCDMSD-V1-L/P

Led Dimmer 12-48VDC 12-24V (15A) 36-48V (10A) IP20

PRODUCT OVERVIEW

The V1-L/P dimming controller delivers smooth 0-100% dimming with 4096 brightness levels and supports single or multi-zone RF 2.4GHz remotes, with up to 10 remotes per controller. It features auto signal transmission for synchronized control, selectable dimming curves and PWM frequency, external push switch input, 3-second fade on/off and built-in safety protection.

PRODUCT INFORMATION

CODE	VOLTAGE INPUT
LCDMSD-V1-L/P	12-48VDC
VOLTAGE OUTPUT	OUTPUT POWER
12-48VDC	480W
OUTPUT CURRENT (PER CH)	CHANNELS
10@36-48V, 15 12-24V	1
DIMMING INPUT	DIMMING OUTPUT
RF, Push	PWM
DIMMING RANGE	PWM FREQUENCY
0-100%	250-8000Hz
REMOTE ENABLED	ZONES
Yes	1
STANDBY LOAD	SAFETY
0.5W	AS/NZS61347 EN55015
PROTECTION	IP RATING
Reverse polarity, over-heat, over-load, short circuit	20
OPERATING TEMP	DIMENSIONS
-30°C to 55°C	L175mm x W45mm x H27mm

DIMENSIONS

