



LCDMXSD-D3-L

DMX Decoder 3Chan X 6A 12-24V IP20

PRODUCT OVERVIEW

The D3-L is a versatile DMX decoder that is compliant with DMX512 protocols, featuring an easy-to-read digital display for quick address setup via onboard controls. With built-in RDM support, the address can also be configured directly from a DMX master console. Adjustable PWM frequency, selectable linear or logarithmic dimming curves, and flexible stand-alone or dimmer modes provide precise lighting control. D3-L offers stand-alone RGB and 3-channel dimmer modes with built-in programs for button control without a DMX signal. Complete with automatic overhear and short-circuit protection for safe, reliable operation.

PRODUCT INFORMATION

CODE

LCDMXSD-D3-L

VOLTAGE OUTPUT

12-24V DC

OUTPUT CURRENT (PER CH)

6A/ch

DIMMING INPUT

DMX

DIMMING RANGE

0-100%

REMOTE ENABLED

Yes

SAFETY

AS/NZS61347 EN55015

IP RATING

20

DIMENSIONS

L170mm x W50mm x H23mm

VOLTAGE INPUT

12-24V DC

OUTPUT POWER

432W

CHANNELS

3

DIMMING OUTPUT

PWM

PWM FREQUENCY

0.5-2kHz

STANDBY LOAD

0.5W

PROTECTION

Reverse polarity, over-heat, short circuit

OPERATING TEMP

-30°C to 55°C

DIMENSIONS

