

LCDMXSD-D4-L

DMX Decoder 4Chan X 5A 12-24V IP20

PRODUCT OVERVIEW

The D4-L is a versatile DMX decoder that is compliant with DMX512 protocols, featuring an easy-to-read digital display for quick address setup via onboard controls. With built-in RDM support, the address can also be configured directly from a DMX master console. Adjustable PWM frequency, selectable linear or logarithmic dimming curves, and flexible stand-alone or dimmer modes provide precise lighting control. D3-L offers stand-alone RGBW and 4-channel dimmer modes with built-in programs for button control without a DMX signal. Complete with automatic overheat and short-circuit protection for safe, reliable operation.



PRODUCT INFORMATION

CODE LCDMXSD-D4-L	VOLTAGE INPUT 12-24VDC
VOLTAGE OUTPUT 12-24VDC	OUTPUT POWER 480W
OUTPUT CURRENT (PER CH) 5A	CHANNELS 4
DIMMING INPUT DMX	DIMMING OUTPUT PWM
DIMMING RANGE 0-100%	PWM FREQUENCY 0.25-32kHz
REMOTE ENABLED No	STANDBY LOAD 0.5W
SAFETY AS/NZS61347 EN55015	PROTECTION Reverse polarity, over-heat, short circuit
IP RATING 20	OPERATING TEMP -30°C to 50°C
DIMENSIONS L170mm x W50mm x H23mm	

DIMENSIONS

