

# LCDMXSD-D5-P

DMX Controller 5chan 20.5A 12-48VDC IP20

## PRODUCT OVERVIEW

A high-performance DMX512 decoder with digital addressing, full RDM control, selectable 8-bit/16-bit dimming, adjustable PWM frequencies, and linear or logarithmic dimming curves. Designed with automatic thermal, overload and short-circuit protection.



## PRODUCT INFORMATION

|                                     |                        |
|-------------------------------------|------------------------|
| <b>CODE</b>                         | <b>VOLTAGE INPUT</b>   |
| LCDMXSD-D5-P                        | 12-48VDC               |
| <b>VOLTAGE OUTPUT</b>               | <b>OUTPUT POWER</b>    |
| 12-48VDC                            | 960W                   |
| <b>OUTPUT CURRENT (PER CH)</b>      | <b>CHANNELS</b>        |
| 5CH, 4A/ch                          | 5                      |
| <b>DIMMING INPUT</b>                | <b>DIMMING OUTPUT</b>  |
| DMX                                 | PWM                    |
| <b>DIMMING RANGE</b>                | <b>PWM FREQUENCY</b>   |
| 0-100%                              | 0.25-32kHz             |
| <b>REMOTE ENABLED</b>               | <b>ZONES</b>           |
| No                                  | 1                      |
| <b>STANDBY LOAD</b>                 | <b>SAFETY</b>          |
| 6W                                  | AS/NZS61347 EN55015    |
| <b>PROTECTION</b>                   | <b>IP RATING</b>       |
| Over-heat, over-load, short circuit | 20                     |
| <b>OPERATING TEMP</b>               | <b>DIMENSIONS</b>      |
| -30°C to 55°C                       | L178mm x W50mm x H38mm |

## DIMENSIONS

