

LCRGBSD-V3

Led Controler 4A X 3Chan 12-24VDC IP20

PRODUCT OVERVIEW

The LCRGBSD-V3 offers flicker-free dimming from 0–100% with 4096 levels of precision. Compatible with single colour, dual colour and RGB/RGBW lighting, this controller supports single or multi-zone setups and up to 10 remotes per unit. Auto-transmitting extends control up to 30m while keeping multiple controllers perfectly synchronised as well as built-in dynamic RGB modes and a selectable 3-second fade.

PRODUCT INFORMATION

CODE LCRGBSD-V3	**VOLTAGE INPUT** 12-24VDC
VOLTAGE OUTPUT 12-24V	**OUTPUT POWER** 288W
OUTPUT CURRENT (PER CH) 4A/ch	**CHANNELS** 3
DIMMING INPUT RF	**DIMMING OUTPUT** PWM
DIMMING RANGE 0-100%	**PWM FREQUENCY** 1kHz
REMOTE ENABLED Yes	**STANDBY LOAD** 0.5W
SAFETY AS/NZS61347 EN55015	**PROTECTION** Reverse polarity, Short circuit
IP RATING 20	**OPERATING TEMP** -30°C to 55°C
DIMENSIONS L97mm x W33mm x H18mm	

While every effort has been made to ensure accuracy, product specifications may vary. Task Lighting reserves the right to update or modify product details without notice.