



LS150-24V-29W-55K

LED Strip Elite 29W/m 24V CRI90 5500K CCIC IP20

PRODUCT OVERVIEW

The LS150 range features constant current single colour LED strips with integrated IC technology, delivering precise current control for stable, uniform brightness across the entire length. Designed for reliable, long lasting performance, the LS150 is ideal for architectural lighting, commercial displays, and interior decorative applications. Compared to our Classic Series, the LS150 supports longer single feed runs while maintaining consistent light output, making it ideal for continuous or large scale installations. Its key advantages include accurate current regulation for uniform illumination and enhanced heat management to maximise lifespan and reliability, making it a dependable choice for professional grade lighting projects.

CONTROL OPTIONS



DIM

Dimmable by PWM

PRODUCT INFORMATION

CODE	LS150-24V-29W-55K	COLOUR TEMP	5000K
WATTAGE	29W/m	VOLTAGE	24
LUMEN OUTPUT	3095lm/m	LED TYPE	SMD
LEDS/M	140	EFFICACY	107lm/W
CRI	90	R9	50
BEAM ANGLE	120°	MAX RUN	5m
OPERATING TEMP	-25°C to 60°C	LUMEN MAINTENANCE	L70B10 @ 50,000 Hrs
DIMENSIONS	12mm × 2.5mm × 50mm		

DIMENSION DRAWING (MM)

