

LEDSL200-5W-3K

Garden Spot Light Series



Technical Parameters

General Data	
Power	6W (draw) 5W LED
CCT	3000K
Lumen output	280 lumens
Beam angle	100°
Dimensions	72dia x 243H (mm) (with spike)
Warranty	2 Years
Dim	No
Electrical Data	
Input voltage	12-24VDC
Cable	500mm rubberised 500mm

Construction Data	
IP rating	IP65 Waterproof
Protection: Finishing	Anodised charcoal (25-30micron)
Fixings	316 stainless steel
Mounting	Adjustable tilt "U"
Accessories	
Spike	Included

Features

- Phillips LEDs
- Powdercoated aluminium and dimpled glass
- Surface mount or garden spike
- Low voltage (constant voltage input)
- Complete with 500mm lead

Applications


- Exterior and garden spot lighting
- High lighting trees, shrubs and pergolas
- General feature lighting
- Water features not total submersion

Note

These lights draw a large inrush current on start up. When selecting drivers use a driver a minimum of 3 times the wattage load of lights.

Example 6 x 6Watts= 36W, 3 x 36W= 108W. Use a 120W driver.

Dimensions



While every effort has been made to ensure the accuracy of all information provided Task Lighting can not be held responsible for any errors. Task Lighting also reserves the right to modify/delete product details without notice.