

IP20 STRIP PACK

9.6W/m 24VDC IP20



Features

- CRI 92+
- Constant Voltage 24VDC
- High density 140LEDs/m
- Complete with pre soldered 0.5mm tails 1m long. 3m, 4m and 5m packs have 1m tails one end and 300mm tails on the opposite end
- Supplied with 3M double sided tape for easy install.
 LED strip must be installed using a TASK Lighting approved mounting profile for warranty purposes
- Dimmable by PWM (Pulse width modulation)


Specification

Watts/m	9.6W/m		
Lumen output	3000K - 720Lm/m 4100K - 780Lm/m 5500K - 840Lm/m		
CRI	92+		
Beam angle	140°		
Cut points	50mm		
Max single feed run	5m		
LEDS/m	140 LEDs/m		
Working temp	-25 ~ 60°C		
Warranty	3 Years		
IP rating	IP20		
Dimmable	Yes (PWM)		

Applications

- Under shelf display lighting
- Under cabinets over benches
- Under bench top returns
- Book shelving

Dimensions



Codes

CCT	1M	2M	ЗM	4M	5M
WW (3000K)	DSL9.6WW24V1M	DSL9.6WW24V2M	DSL9.6WW24V3M	DSL9.6WW24V4M	DSL9.6WW24V5M
NW (4100K)	DSL9.6NW24V1M	DSL9.6NW24V2M	DSL9.6NW24V3M	DSL9.6NW24V4M	DSL9.6NW24V5M
W (5500K)	DSL9.6W24V1M	DSL9.6W24V2M	DSL9.6W24V3M	DSL9.6W24V4M	DSL9.6W24V5M

While every effort has been made to ensure the accuracy of all information provided Task Lighting can not be held responsible for any errors. Task Lighting also reserves the right to modify/delete product details without notice.