

IP66 STRIP PACK

9.6W/m 24VDC IP66



Features

- CRI 92+
- Constant Voltage 24VDC
- High density 140LEDs/m
- Complete with pre soldered 0.5mm tails (clear) 1m long
- Supplied with 3M double sided tape for easy install. LED strip must be installed using a TASK Lighting approved mounting profile for warranty purposes
- Dimmable by PWM (Pulse width modulation)


Specification

Watts/m	9.6W/m	
Lumen output	3000K - 720Lm/m Silicone sleeves cause a colour shift of approx +200K	
Beam angle	120°	
Cut points	50mm	
Max single feed run	5m	
LEDS/m	140 LEDs/m	
Working temp	-25 ~ 60°C	
Warranty	3 Years	
IP rating	IP66	
Dimmable	Yes (PWM)	

Applications

- Under exterior bench seating
- Under exterior stair treads
- Under eves
- Bathrooms
- Pergolas

Dimensions



Note: End caps are bigger than the silicone sleeve & sealed by silicone adhesive these add around 2mm to the width shown above.

Codes

CCT	2M	3M	5M
WW (3000K)	DSLE9.6WW24V2M	DSLE9.6WW24V3M	DSLE9.6WW24V5M

While every effort has been made to ensure the accuracy of all information provided Task Lighting can not be held responsible for any errors.

Task Lighting also reserves the right to modify/delete product details without notice.