

Specifiers Linear Series - LS131 - CRI95





CRI 95
19.2W 24V
IP20 DIM
240LED/m
25mm 24V

19.2W - High Density 240LEDs/m - Dot Free

SPECIFICATION			
COLOUR	Warm White	Neutral White	White
CODE	LS131WW24-CRI95	LS131NW24-CRI95	LS131W24-CRI95
WATTS	19.2W/m		
VOLTS INPUT	24VDC	24VDC	24VDC
AMPS INPUT	0.8Amps/m		
COLOUR TEMP	3000K	4000K	5500K
CRI	CRI>95		
LUMENS	1299lm/m	1536lm/m	1632lm/m
BEAM ANGLE	120deg		
IP RATING	IP20 Indoor Use Only		
DIM PWM	Yes		
WORKING TEMP	-25 to +60deg C		
LED	Epistar 3528		
EXPECTED LIFE	25,000hrs **		
WARRANTY	2years **		
MAX RUN LENGTH	5m		
LED PITCH	4mm & 240 LEDs/m		
CUT LENGTH	25mm (6 LEDs)		
FIXING	3M doubled sided tape		
CONNECTION	2 x 20AWG wire		

DIMENSIONS



FEATURES

- High density 240 LEDs/m
- Specifically designed to be dot free in shallow profiles and channels with an opal lens giving a totally even illumination like fluorescent or neon

APPLICATIONS

- Anywhere high colour rendering is essential
- Clothing & shoe shops
- Art galleries & museums
- Cabinet and display lighting

NOTE

This linear LED product must be installed in an appropriate TASK Lighting or similar approved LED mounting profile/channel to dissipate heat. Failure to do so may result in a much shortened LED life, colour shift and void the warranty.

While every effort has been made to ensure the accuracy of all information provided Task Lighting can not be held responsible for any errors. Task Lighting also reserves the right to modify/delete product details without notice.