

LS200


RGB 48V Interior LED Strip



Features

- Ideal for long single feed runs
- High efficacy up to 50Lm/w
- 5 year warranty
- PWM Dimmable

Dimensions



Specification

| Code | LS200-48V-8W-RGB | | | | LS200-48V-15W-RGB | | | | LS200-48V-24W-RGB | | | |
|------------------|---------------------|-------|-------|----------|-------------------|-------|-------|-------------|-------------------|-------------------------|-------|---------|
| W/m | 8W | | | | 15W | | | | 24W | | | |
| Wave Length (nm) | RGB=480 | R=620 | G=525 | B=465 | RGB=480 | R=620 | G=525 | B=465 | RGB=480 | R=620 | G=525 | B=465 |
| Lm/m | 393 | 71 | 270 | 52 | 750 | 135 | 510 | 100 | 1200 | 216 | 816 | 160 |
| Max Run | 15m | | | | 12m | | | | 9m | | | |
| Binning | +/-5nm | | | | | | | | | | | |
| Operating Temp | -25 to 65°C | | | | | | | | | | | |
| Ambient Temp | -25 to 45°C | | | | | | | | | | | |
| Expected Life | L70B10 @ 50,000hrs | | | | | | | | | | | |
| Voltage | 48VDC (47 to 49VDC) | | | LED Type | | 3838 | SMD | IP R | ating | 20 | | |
| LEDs/m | 216 | | | Cut | Points | 55.5 | 5mm | Copper Tape | | 2oz | | |
| Min Bend Radius | 50mm | | | Dim | Dimming | | VM | Instal | lation | 3M 300LSE adhesive tape | | dhesive |

While every effort has been made to ensure the accuracy of all information provided Task Lighting can not be held responsible for any errors.

Task Lighting also reserves the right to modify/delete product details without notice.