


# RGB High Density 216LED 48V


Spot free RGB high efficacy LED strip. Features longer lifespan, high efficacy. Designed to provide consistent linear lighting in a wide variety of applications for cove lighting and indirect lighting in hotels, restaurants, shops, offices and homes.  
48V allows for longer single feed runs

## Features

- High efficacy up to 50Lm/w
- 3838RGB, 216LED/m, 48V
- 5 years warranty
- PWM Dimmable



## Cut Points



## Technical Data

Model	LS220-RGB-8W				LS220-RGB-15W				LS220-RGB-24W			
W/m	8W				15W				24W			
Wave Length (nm)	RGB=480	R=620	G=525	B=465	RGB=480	R=620	G=525	B=465	RGB=480	R=620	G=525	B=465
Lm/m	393	71	270	52	750	135	510	100	1200	216	816	160
Max Run	15m				12m				9m			
Binning	+/-5nm											
Operating Temp	-25 to 65degC											
Ambient Temp	-25 to 45degC											
Expected Life	50,000hrs											
Voltage	48VDC (47 to 49VDC)			LED Type	3838 SMD			IP Rating	20			
LEDs/m	216			Cut Points	55.55mm			Copper Tape	2oz			
Min Bend Radius	50mm			Dimming	PWM			Installation	3M 300LSE adhesive tape			

While every effort has been made to ensure the accuracy of all information provided Task Lighting can not be held responsible for any errors. Task Lighting also reserves the right to modify/delete product details without notice.