

PSTW Series 12V - Large Terminals

Drivers Constant Voltage



SPECIFICATION								
CODE	PSTW-12V-12W	PSTW-12V-20W	PSTW-12V-40W	PSTW-12V-50W	PSTW-12V-60W	PSTW-12V-75W	PSTW-12V-100W	PSTW-12V-150W
WATTS OUTPUT	1-12Watt	1-20Watt	1-40Watt	1-50Watt	1-60Watt	1-75Watt	1-100Watt	1-150Watt
VOLTS OUTPUT	12Volts DC							
AMPS OUTPUT	1.0Amps	1.7Amps	3.3Amps	4.2Amps	5.0Amps	6.3Amps	8.36Amps	12.5Amps
VOLTS INPUT	220-240VAC 50~60Hz							
POWER FACTOR	0.80	0.80	0.95	0.95	0.95	0.95	0.95	0.95
IP RATING	IP20							
DIMENSIONS	98 x 39 x 22	113 x 44 x 28	166 x 52 x 24	184 x 61 x 32	184 x 61 x 32	184 x 61 x 32	184 x 61 x 32	210 x 67 x 34
PROTECTION	Safe no load, Short circuit, Over temp, Class II, SELV.							
WORKING TEMP	-20 to +50degC						-20 to +45degC	-20 to +45degC
EMC	EMC compliant							
SAFETY	Tested to AS/NZS requirements							
WARRANTY	3 Years							

Features

- Large terminals for looping TPS
- Covered 230V terminals
- SELV & Class 2
- Warranty 3 years

Applications

- Power 12VDC LED strips & lamps
- Suitable for supplying power to 12VDC dimmed loads like PWM (pulse width modulation) dimmed loads & 12VDC RGB colour changing loads

NOTE: IP20 for indoor use only or exterior when housed in a suitable enclosure for exterior use.
Do not cover with insulation and allow for good ventilation.

While every effort has been made to ensure the accuracy of all information provided Task Lighting can not be held responsible for any errors.
Task Lighting also reserves the right to modify/delete product details without notice.