

LS220 RGBW

48VDC Interior & Exterior LED Strip


The LS220 RGBW 48V LED Strip offers seamless, linear lighting for a wide range of applications, including cove and indirect lighting in hotels, restaurants, retail stores, offices, and homes. Its 48V design allows for longer single-feed runs while reducing voltage drop, ensuring consistent and reliable performance.

Features

- Suitable for long runs reducing voltage drop
- High efficacy up to 46Lm/W
- Dimmable by PWM, 0-10V, DALI, DMX
- 5 Year Warranty



Dimensions



Technical Information

| Code - IP65 Sleeve | LS220E-RGBW3K-20W | | LS220E-RGBW6K-20W | |
|----------------------|-------------------|---------|-------------------|----------|
| Code - IP20 Interior | LS220-RGBW3K-20W | | LS220-RGBW6K-20W | |
| Wattage | 20W/m | | | |
| Wave Length (nm) | RGBW 476 | Red 622 | Green 525 | Blue 468 |
| Lumen Output | 800Lm/m | 110Lm/m | 312Lm/m | 92Lm/m |
| Max Single Feed Run | 10m | | | |
| Operating Temp | -25° to 65°C | | | |
| Ambient Temp | -25° to 45°C | | | |
| Lumen Maintenance | L70 @ 50,000hrs | | | |
| Voltage | 48VDC | | | |
| LEDs/m | 120 | | | |
| Min Bend Radius | R > 30mm | | | |
| LED Type | 5050 | | | |
| Cut Points | 100mm | | | |
| Dimming | PWM/0-10V/DALI | | | |

This linear LED product must be installed in an appropriate TASK Lighting or similar approved LED mounting profile/channel to dissipate heat. Failure to do so may result in a much shortened LED life, colour shift and void the warranty. End caps are bigger than the silicone sleeve & sealed by silicone adhesive which is supplied separately. Silicone sleeves cause a colour shift of approx +200K.

While every effort has been made to ensure the accuracy of all information provided Task Lighting can not be held responsible for any errors.

Task Lighting also reserves the right to modify/delete product details without notice.