


LS300S

RGB + Tuneable White IP54 COB Strip



The RGB+TW COB LED strip delivers a broad colour spectrum, offering flexibility for diverse lighting effects in applications such as architectural accent lighting, entertainment spaces, and home automation for dynamic illumination.

With RGB+TW technology, you can colour mix with red, green, and blue as well as adjusting the white light separately from 2700K to 6500K.

Features

- Uniform light output without visible hotspots, resulting in a smooth, continuous line of light.
- Flexible PCB ideal for bending and curving not exceeding the minimum bend diameter.
- Dimmable by PWM offering a wide range of brightness levels that can be adjusted based on your preference or environmental needs.

Specification

Code	LS300S-24V-25W-RGBTW
Colour	RGB + TW 2700-6500K
Volts Input	24V Constant Voltage
Watts/m	25W/m
Lumen Output	White - 1100Lm/m @ 4K
LED type	2412
LEDs/m	840
Cut Segment	41.6mm
Max Run	5m single feed
Connection	0.5mm ² 6 core tail
IP Rating	IP54 Silicone Spray
Dimmable	Yes (PWM, DALI, 0/10V, Triac)
Operating Temp	-20°C ~ 60°C
Beam Angle	120°
Bend Radius	R<50mm
Lumen Maintenance	L70B10 @ 50,000hrs
Warranty	5 Years

Dimensions

